

Technical data sheet

Foamed plastic joint tape

one-sided, self-adhesive foam joint tape

Art.-No.: **FKBANDS**



Product

Description: Self-adhesive polyurethane foam tape for sealing formwork.

Uses: Foamed plastic joint tape for use in places that are not easily accessible.
Not suitable for use in drinking water installations.

Product Data

Techn. features	Material	white, open-pored polyurethane foam
	Bulk density	18 kg/m ³
	Strip thickness	6 mm
	Band width	19 mm
	Adhesive	Hot melt adhesive made of synthetic rubber
	Protective coating	Foil, white
	Pull-out resistance	≥ 5 N/25 mm, (Separation of the foam) (acc. to DIN EN 1939)
	Shear strength	500 g/ 625mm ² (acc. to DIN EN 1943)
	Recommended installation temperature	+10°C to +30°C
	Heat resistance	-30°C to +80°C
	Resistance to condensation water	high
	Resistance to ageing	limited
	Resistance to oxidation	limited

Packaging:	roll - 10m length Carton with 15 rolls
Storage:	36 months from production date, originally packed in an unopened and undamaged carton. Store between +5°C and 25°C. Protect from UV radiation.

Disclaimer / Notes:

All technical data stated in this TDS are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control. Recommendations with regard to product application given in the present technical data sheet for practical assistance of product users are based on our experience and our present scientific and practical body of knowledge. These recommendations, however, are given without engagement and do not establish a contractual relationship or subsidiary duties. These recommendations do not relieve users of their liability and of their own responsibility to test, whether our product is adequate for the intended purpose of application. Please refer to the latest edition of this Technical Data Sheet on our web presence www.maxfrank.com